

# 5274 PASSIVE PLANETARY FLOOR PREPARATION SYSTEM

with Quick-Change Magnetic Tooling



Magnetic tooling easily snaps into place



## 5274 SPECIFICATIONS

Width	16.5"	42 cm
Disk Size	16"	41 cm
Max. Height	47.5"	121 cm
Min. Height	17"	43 cm
Max. Length	66.5"	169 cm
Min. Length	23.75"	60 cm
Weight	171 lb	77.6 kg
Drum RPM	301	
Motor RPM	1793	
Voltage	115	
Frequency	60 Hz	
Motor Phase	Single	
HP	1.5	1.1 kW

## FEATURES

Designed for small jobs and hard to reach spaces, this patented passive planetary operation creates the perfect profile for new coatings. Built rental tough, the 5274 is easy to operate and low maintenance. The versatility of the 5274 is derived from its quick-change magnetic tooling to remove thin-set, coatings, adhesives, remove high spots, and prepare concrete and overlays for coatings.

- A. Handle-lever start
- B. HD strain relief
- C. Power cord plugs into any 115-volt outlet
- D. Handle and head separate in seconds for easy mobility and transport in any vehicle
- E. Safety disconnect motor cord guarantees the machine will always be off during tooling changes
- F. 16-inch grinding plate; head rotates 180 degrees for easy tooling changes; floating deck enables the magnetic tooling plate to contour against any surface, creating a uniform scratch pattern for coating applications or for polishing concrete with surface variation
- G. Adjustable velcro dust guard lets the machine operate within 1/8-inch of walls and promotes nearly dustless operation
- H. 1.5 HP motor runs at less than 15 amps through a 115-volt power source



Operates within 1/8" of walls  
Pictured: 8274-4

## Included with the 5274

- 401582: Passive planetary tooling mounts (3 each)
- 9245: Velcro adapter (3 each)
- 5274-45: Adjustable dust guard
- 7261: Deluxe grind and scrape plate
- 72610: 30-foot, 12-gauge extension cord
- Instruction manual