## **8000** PROPANE-POWERED RIDE-ON SCRAPER





Pictured: 57

8000 SPECIFICATIONS		
Width*	30"	76 cm
Height	61"	155 cm
Length*	63"	160 cm
Weight**	2,887 lb	131 kg
Removable Weight	1,003 lb front, 75 lb rear	455 kg front, 34 kg rear
Weight (machine only)	1,809 lb	820.6 kg
Speed	up to 200 ft/min	up to 61 m/min
HP	25	19.1 kW

\*Measurements are without tooling attached

 $^{\ast\ast}\mbox{Weight}$  may vary depending on fill level and size of propane tank on machine.

## FEATURES

This 2,950-pound scraper rivals 3,500-pound units. Different from hydrostat-powered units, the 8000 combines National's patented carbide angle-shank technology with the added efficiency of dual-lift hydraulic slide-plates. Consistent torque sets the operational standard for high removal rates, and each machine undergoes a rigorous quality assurance program including emissions certification.

- A. Adjustable seat with armrests
- B. Automatic kill switch is triggered when the operator seat is vacant
- C. Precise hydraulic steering for maneuvering in tight spaces, zero turn-radius, and continuous torque for higher removal rates and greater productivity
- D. Ergonomic design includes movable foot pegs and an adjustable operator's seat position for optimal comfort and line of sight; slide plate provides an additional 200 pounds of down pressure on the cutting head
- E. Quick-change swivel head
- **F.** Dual-lift, hydraulic slide-plate adjusts blade pitch and angle for continuous contact with the floor; standard on every 8000
- G. Larger/deepened forklift pockets
- H. Copious 21-inch non-marking tires
- I. E-stop knob for safety
- J. Liquid-cooled Kawasaki engine is re-engineered with National's exclusive catalytic design for the industry's lowest emissions
- K. Hinged hood system for easy-access maintenance
- L. Compact design fits through standard door frames and elevator doors
- M.New front cast slide-plate and debris deflector
- N. Hydraulic lock-out break system automatically engages when the machine is in the off position

## Included with the 8000

- 7050-6: 6-inch cutting head
- $\cdot$  7050-10: 10-inch cutting head
- 7050-12: 12-inch cutting head
  6260-BD: 6-inch .094 bevel
- down self-scoring blade
- 6277: 12-inch .094 bevel up self-scoring blade
- 6284: 12-inch .094 heavyduty blade
- 6285: 6-inch .094 heavyduty blade
- 6286: 10-inch .094 heavyduty blade
- 7077-8: 8-inch tapered cutting head shank blade
- 7079-2: 2-inch angle shank with carbide tip
- 7079-6: 6-inch angle shank with carbide tip
- 5110-100: Front-wheel assembly

- 74854: Weight, 37 pounds (10) (front)
- 400197: Weight, 28 pounds
   (11) (front)
- 401960: Weight, 84 pounds 4) (front)
- 5110-404: Weight, 75 lb (1) (rear)
- 7050-P: Propane tanks (2)
- 75007: CO detector (2)
- 75008: Clip (2)
- 5700-88: Hour meter
- 75005: Fire extinguisher
- 1009: Safety glasses
- 70549: Wrench
- 20lb tank; 33lb (forklift size) propane tank conversion brackets available on special order
- Instruction manual
- One-year manufacturer's warranty on parts and labor