

5200QL QUICK-LOAD CORDLESS RIDE-ON SCRAPER

5200QLW (European model)



FEATURES

The 5200QL is the only slide-out, replaceable-battery machine in the industry with a rear-accessed battery pack that is easily installed, changed, and transported. With no belts or gears, this scraper boasts low maintenance costs while maximizing production. Great for commercial surface removal and preparation, it is quiet and compact enough for residential jobs.

- A. Adjustable seat
- B. Automatic kill switch is triggered when the operator seat is vacant
- C. Control lever with forward/reverse/neutral/break
- D. Ergonomic design includes movable foot pegs and adjustable slide-plate that correct the operator's seat position for optimal comfort and line of sight
- E. Quick-change swivel head
- F. Extra weight compartments
- G. Larger/deepened forklift pockets
- H. Non-marking tires
- I. E-stop knob for safety
- J. Trailer hitch
- K. Rear weight compartment
- L. Flip-up back lid for quick and easy battery changing
- M. New front cast slide-plate and debris deflector

Included with the 5200QL

- 7050-6: 6-inch cutting head
- 7050-10: 10-inch cutting head
- 7050-12: 12-inch cutting head
- 6260-BD: 6-inch .094 bevel down self-scoring blade
- 6277: 12-inch .094 bevel up self-scoring blade
- 6284: 12-inch .094 heavy-duty blade
- 6285: 6-inch .094 heavy-duty blade
- 6286: 10-inch .094 heavy-duty blade
- 5110-404: weight 75 pounds (1) (Rear)
- 5110-100: Front wheel assembly
- 74854: Weight, 37 pounds (5) (Front)
- 6254: 50-foot, 12-gauge extension cord (2)
- 5200QL-500: Two transport carts - 5200QL only
- 5204: Power Pack (one pack on the machine and one additional)
- 5212: 48-volt battery charger
- 7077-8: 8-inch tapered cutting head shank blade
- 7079-2: 2-inch angle shank with carbide tip
- 7079-6: 6-inch angle shank with carbide tip
- 70549: Wrench
- 1009: Safety glasses
- Instruction manual
- One-year manufacturer's warranty on parts and labor



All of National's ride-on scrapers fit through standard doorways.
Pictured: 5700

5200QL SPECIFICATIONS

Width*	24.75"	63 cm
Height	46.5"	119 cm
Length*	57"	145 cm
Weight	1,760 lb	798.3 kg
Removable Weight	370 lb front, 75 lb rear	167.8 kg front, 34 kg rear
Weight (machine only)	1,315 lb	596.5 kg
Speed	up to 120 ft/min	up to 36.6 m/min
Voltage	115/230	
Frequency	60/50 Hz	
HP	4	2.98 kW

*Measurements are without tooling attached