

5700 ALL DAY BATTERY RIDE-ON MACHINE

5700HS, 5700W (European model)



FEATURES

Built to operate on almost any job site, the 5700 will power through an 8- to 12-hour day on a single charge. Its built-in 115-volt charging system can plug into any outlet, and there are no harmful fumes or hazardous by-products. Remove the weights to meet passenger elevator weight maximums or to fit through 30-inch doors.

- A. Adjustable seat
- B. Automatic kill switch is triggered when the operator seat is vacant
- C. Precise hydraulic steering for maneuvering in tight spaces, zero turn-radius, and continuous torque for higher removal rates and greater productivity
- D. Ergonomic design includes movable foot pegs and adjustable slide-plate that correct the operator's seat position for optimal comfort and line of sight
- E. Quick-change swivel head
- F. Optional dual-lift, hydraulic slide-plate adjusts blade pitch and angle for continuous contact with the floor
- G. Larger/deepened forklift pockets
- H. Non-marking tires
- I. E-stop knob for safety
- J. AGM (Absorbed Glass Matt) batteries provide 100 percent power, speed, and torque for 90 percent of the batteries' run cycle
- K. Removable hood system for easy-access maintenance
- L. Compact design fits through standard door frames and elevators doors, removing the weights allows the 5700 to meet the maximum standard elevator weight restrictions
- M. New front cast slide-plate and debris deflector

Included with the 5700, 5700W, 5700HS

- 7050-6: 6-inch cutting head
- 7050-10: 10-inch cutting head
- 7050-12: 12-inch cutting head
- 6260-BD: 6-inch .094 bevel down self-scoring blade
- 6277: 12-inch .094 bevel up self-scoring blade
- 6284: 12-inch .094 heavy-duty blade
- 6285: 6-inch .094 heavy-duty blade
- 6286: 10-inch .094 heavy-duty blade
- 7077-8: 8-inch tapered cutting head shank blade
- 7079-2: 2-inch angle shank with carbide tip
- 7079-6: 6-inch angle shank with carbide tip
- 5110-100: Front-wheel assembly
- 74854: Weight, 37 pounds (10) (Front)
- 1009: Safety glasses
- 73507-1: 7-foot, 12-gauge extension cord
- 70549: Wrench
- Instruction manual
- One-year manufacturer's warranty on parts and labor



5700/5700HS SPECIFICATIONS

Width*	24.5"	62 cm
Height	50.5"	128 cm
Length*	58.5"	149 cm
Weight	2,244 lb	1,017.9 kg
Removable Weight	185 lb front	83.9 kg front
Weight (machine only)	2,059 lb	933.9 kg
Speed	up to 120 ft/min 160 ft/min for HS	up to 36.6 m/min 48.8 m/min for HS
Voltage	115/230	
Frequency	60/50 Hz	
HP	4	2.98 kW

Meets declaration of conformity standards and is CE certified

*Measurements are without tooling attached

5700HS: Designed to cover more space in less times, specifications made to order.