

6280HD

Gladiator

HYDRAULIC WALK-BEHIND SCRAPER



6280HD SPECIFICATIONS

Width	17.75"	45 cm
Max Height	46.75"	119 cm
Height (handle folded)	29.75"	76 cm
Max. Length	49.5"	126 cm
Length (handle folded)	29.5"	75 cm
Weight	490 lb	222.3 kg
Removable Weight	78 lb front, 43 lb side	35.4 kg front, 19.5 kg side
Weight (machine only)	369 lb	167.4 kg
Speed	up to 30 ft/ min	9.1 m/min
RPM	1725/1425	
Voltage	115/230	
Frequency	60/50 Hz	
HP	1.5	1.12 kW
Amps (full load)	14.7/10.5	

Meets declaration of conformity standards and is CE certified

FEATURES

The 6280HD removes the worst of today's hard goods such as glued down floors, gummy commercial carpet, VCT, sheet vinyl, rubber tile, linoleum, indoor and outdoor sport surfaces, roofing material, and more. Its compact design makes it ideal for use in confined spaces, while the side slide-weights add extra head pressure when forward and improved traction when moved over the back wheels. This unit is designed to take up soft and hard goods, such as tile, wood flooring, and thin-set.

- A.** Ergonomically designed, adjustable-position hand grips; hydraulic forward drive; self-propelled reverse drive; variable speed 10 to 45 feet per minute; optional manual drive with removal of drive pins; system for throttle/speed control and smooth transitions
- B.** Six handle positions for work under racks and in other confined areas; collapses to save space during transport and storage
- C.** Self-contained, limited-maintenance hydraulic fluid
- D.** Lifting bail
- E.** Secure-mount side slide-weights adjust scraper-head pressure; Side slide-weights add extra head-pressure when forward, and improved traction when moved over the back wheels
- F.** New rounded front-weight design better deflects loose material during use
- G.** Adjustable, self-cleaning, industrial-grade wheels disengage by clip-pin removal for easy non-powered maneuvering
- H.** Motor equipped with thermal-overload protection circuit-breaker to eliminate unnecessary strain and electrical overload
- I.** Oscillating action rotates the cutting blade to cut through a range of materials over various substrates; extends life cycle of machine while reducing maintenance costs

Included with the 6280HD

- 6254: 50-foot, 12-gauge extension cord
- 6258-BU: 3" x 12" blade
- 6276-BU: 3" x 10" heavy-duty blade
- 6280HD-250: Transport-wheel assembly
- 7050-200: 3" x 6" premium blade
- 7050-202: 3" x 10" premium blade
- 7050-203: 3" x 12" premium blade
- 7050-204: 3" x 14" premium blade
- 6280-401B: 7/32 t-handle wrench
- 7280-2B: 22-degree angle attachment
- 7280-2C: 30-degree angle attachment
- 7280-6: 6-inch cutting head
- 7280-12: 12-inch cutting head
- 7281-2: 2-inch carbide shank
- 7280-4: Retainer cap assembly
- 1009: Safety glasses
- Instruction manual
- One-year manufacturer's warranty on parts and labor